



④	防塵蓋	5pcs	透明
③	TERMINATOR	1PCS	插拔式 LVD/SE ULTRA-320MB (33.2*47.9mm)
②	插頭	6pcs	SCSI 68P 黑色全塑公頭
①	線材	1PCS	SHOWA UL2734 30AWG 34TWISTED PAIRS(1P:紅/白 33P:藍/白) PH:0.635MM SPAN:135mm L=920MM
NO.	NAME	Q'TY	DESCRIPTION

Test Condition  
 1.100% Open/Short  
 2.Contact Resistance:20m Ohm Max  
 3.Insulation Resistance:10M hom Min  
 3. HI-POT: 300V 10MS.

1.3			
1.2			
1.1			
1.0	RELEASED	Cel Wang	07-Dec-2006
REV.	ECN. NO.	DR.BY	DATE



MAT'L: FINISH:

x.: ±0.30	x': ±5.0'
x.x: ±0.20	x.x': ±3.0'
x.xx: ±0.15	x.xx': ±1.0'
UNIT: mm	
SCALE: 1:1	SHEET: 1/1

TITLE : Connector&Cable Assembly		A4
APPD.:	PRAT NO : ASS-C-523	
CHKD.:	DWG. NO.: 20061207-04(HK)	
DR.: Cel Wang	REV.: 1.0	DATE: 07-Dec-2006