



接點示意圖:

P1 (RED)	P2 (GRAY)	P3 (BLACK)
1	1	1
3	3	3
4	4	4
5	5	5
6	6	6
7	7	7
.	.	.
18	18	18
(第20Pin塞Key)	20	20
21	21	21
23	23	23
25	25	25
27	27	27
28	28	28
29	29	29
31	31	31
32	32	32
33	33	33
.	34	34
35	35	35
36	36	36
37	37	37
38	38	38
39	39	39
GROUND PIN		
2	2	2
19	19	19
22	22	22
24	24	24
26	26	26
30	30	30
34	40	40
40		

NO.	NAME	Q'TY	VENDER	DESCRIPTION
④	插頭	1SET	佳霖	ATA 40P 有耳 有塞(第20Pin塞Key) 黑色 三件
③	插頭	1SET	佳霖	ATA 40P 有耳 有塞(第20Pin塞Key) 灰色 二件
②	插頭	1SET	佳霖	ATA 40P 有耳 有塞(第20Pin塞Key) 紅色 三件
①	線材	IPC	福康	UL2678 30AWG 80C PH:0.635MM PVC灰色排線 L=470MM

Test Condition  
 1.100% Open/Short  
 2.Contact Resistance:5m Ohm Max  
 3.Insulation Resistance:5M hom Min  
 3. HI-POT: 300V 10MS.

1.3				<b>崧嵐企業有限公司</b> <b>TOWNES ENTERPRISE CO., LTD.</b>	x.: ±0.30	x': ±5.0'	TITLE :	<b>A4</b>
1.2			MAT'L:		x.x: ±0.20	x.x': ±3.0'	40P-40P IDC Connector Assembly	
1.1			FINISH:		UNIT: mm	x.xx': ±1.0'	APPD.:	
1.0	RELEASED	Cel Wang	07-Dec-2006		SCALE: 1:1	CHKD.:	DRG. NO.: 20061207-04(HK)	
REV.	ECN. NO.	DR.BY	DATE		SHEET: 1/1	DR.: Cel Wang	REV.: 1.0	DATE: 07-Dec-2006